

Stainless Steel Electrical Griddle

Table Top




EG 1750


EG 3000

EG 3500


EG 5250



Side View




Front View




Side View



Front View



Side View



Front View



Front View


Free Standing



EG 3000FS

EG 3500FS


EG 5250FS



Side View



Front View



Side View



Front View



Front View

- Stainless steel body.
- Temperature range 50°C to 300°C.
- 1, 2 to 3 tubular heaters of 1750 watt each.

- 9mm / 12mm thick, flat polished steel griddle plate.
- Removable stainless steel grease drip pan with drain holes.

	EG 1750	EG 3000	EG 3500	EG 5250	EG 3000FS	EG 3500FS	EG 5250FS
Hot Plate Size (mm)	395 x 333 x 9	600 x 330 x 12	600 x 415 x 12	900 x 415 x 12	600 x 330 x 12	600 x 415 x 12	900 x 415 x 12
Machine Dimension (mm)	400 x 455 x 280	600 x 455 x 288	600 x 600 x 400	900 x 600 x 400	600 x 455 x 930	600 x 600 x 930	900 x 600 x 930
Machine Weight (kg)	17	26	41	57	31	43	61
Packing Dimension (mm)	540 x 460 x 320	660 x 540 x 320	700 x 677 x 345	957 x 717 x 400	660 x 540 x 320	774 x 660 x 405	953 x 770 x 405
Rated Voltage (V)	220 ~ 240	220 ~ 240	220 ~ 240	380 ~ 415	220 ~ 240	220 ~ 240	380 ~ 415
Rated Wattage (W)	1,750	3,000	3,500	5,250	3,000	3,500	5,250
Frequency (Hz)	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60	50 / 60
Phase	1	1	1	3	1	1	3
Packing Vol (m ³)	0.05	0.11	0.21	0.30	0.11	0.21	0.30