



Stainless Steel Gas Deep Fryer Economic


Free Standing



Front View




Side View



Top View



Honey Comb Burner



Tube-Fire Heating System



FSGDF23M-1B



FSGDF23M-2B

- Body – Full stainless steel constructed body, hygienic and easy to keep clean.
- Chrome plated mesh basket.
- Stainless steel grid screen and drain pipe.
- Burner with high thermal efficiency, low carbon monoxide emission.

- Equipment with thermocouple. If fire accidentally goes off, this safety device will automatically cut off gas supply.
- Equipped with high limit safety device. Burner will automatically go off if oil temperature exceed 230°C.
- The thermostat control allows is to select our ideal cooking temperature.
- Suitable for LPG and NG.

Model	Product Dimension (L x W x H) (mm)	Packing Dimension (L x W x H) (mm)	Tank Capacity (Litres)	Basket Dimension (L x W x H) (mm)	Weight (kg)	Consumption Btu / Hr (MJ / Hr)
FSGDF23M-1B	405 x 780 x 1105	460 x 860 x 1080	23	305 x 330 x 135	44	78000 (82.7)
FSGDF23M-2B	405 x 780 x 1105	460 x 860 x 1080	23	156 x 330 x 147	45	78000 (82.7)


Stainless Steel Tempura Fryer



TF 24




Filtration Basket and Container




Tube-Fire Heating System



FRONT VIEW



SIDE VIEW



TOP VIEW

- Body – Full stainless steel constructed body, hygienic and easy to keep clean.
- Burner with high thermal efficiency, low carbon monoxide emission.
- Equipped with thermocouple. If fire accidentally goes off, this safety device will automatically cut off gas supply.
- Equipped with high limit safety device. Burner will automatically go off if oil temperature exceed 230°C.
- The thermostat control allows selection of ideal cooking temperature.
- Suitable for LPG and NG.
- Filtration basket and container.
- Side tray provided.

Model	Product Dimension (L x W x H) (mm)	Packing Dimension (L x W x H) (mm)	Tank Capacity (Litres)	Weight (kg)	Gas Consumption Btu / Hr (MJ / Hr)	Volumn (m3)
TF 24	550 x 600 x 1070	600 x 660 x 1020	34	45	30000 (31.8)	0.4